

Datasheet - PH-COM4-ER-04

Safety light curtains, Safety light grids / Accessories / protective enclosure for Safety light grids and curtains / PH-COM4-ER-xx



(Minor differences between the printed image and the original product may exist!)

Ordering details

Product type description	PH-COM4-ER-04
Article number	103026843
EAN Code	
eCl@ss	

Global Properties

Product name	Schutzgehäuse IP69K
Materials	
- Material of the housings	Polycarbonate
-	PA6
Weight SLC/SLG	2.8 ... 3.3 kg

Mechanical data

Design of electrical connection	cable gland fixed integrated
- Wiring of the transmitter	connector plug M12, 4-pole
- Wiring of the receiver	connector plug M12, 8-pole
Cable length	10 m

Ambient conditions

Ambient temperature	
- Min. environmental temperature	-10 °C
- Max. environmental temperature	+50 °C
Storage and transport temperature	
- Min. Storage and transport temperature	-25 °C
- Max. Storage and transport temperature	+70 °C
Protection class	IP69K to IEC/EN 60529

Dimensions

Dimensions	
- Durchmesser	50 mm
- Durchmesser End plugs	60 mm
- Height	1370 ... 1770 mm

Documents

Operating instructions (fr) 398 kB, 05.04.2019

Code: mrl_sh-ph-440_fr

Operating instructions (en) 428 kB, 22.01.2020

Code: mrl_sh-ph-440_en

Operating instructions (es) 403 kB, 28.03.2019

Code: mrl_sh-ph-440_es

Operating instructions (pt) 404 kB, 22.03.2019

Code: mrl_sh-ph-440_pt

Operating instructions (de) 412 kB, 22.01.2020

Code: mrl_sh-ph-440_de

Operating instructions (nl) 344 kB, 17.10.2019

Code: mrl_sh-ph-440_nl

Brochure (it) 2 MB, 01.03.2018

Code: b_optoshort_it

Brochure (pt) 2 MB, 26.10.2018

Code: b_optoshort_pt

Brochure (es) 2 MB, 23.10.2018

Code: b_optoshort_es

Brochure (fr) 2 MB, 20.11.2018

Code: b_optoshort_fr

Brochure (en) 2 MB, 23.10.2018

Code: b_optoshort_en

Brochure (pl) 2 MB, 20.02.2019

Code: b_optoshort_pl

Brochure (de) 2 MB, 22.10.2018

Code: b_optoshort_de

ECOLAB certification (de, en) 1 MB, 05.02.2019

Code: z_sh4p01

Images

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The data and values have been checked thoroughly. Technical modifications and errors excepted.

Generiert am 28.02.2020 - 17:24:00h Kasbase 3.3.0.F.64l